

## MPB SERIES CP100 CALIBRATION CYLINDER

### GENERAL INFORMATION

This range of precision calibration cylinders has been designed to meet the requirements of high accuracy and robust construction and is particularly suited to offshore and onshore petrochemical installations.

This product range can be supplied with either threaded or flanged connections to customer requirements.

The MPB Series CP100 Calibration Cylinder is ideal for use as a pump setting gauge, or pump rate checking.

Materials of construction include 316 Stainless steel, Super Duplex Stainless steel, Titanium, Hastelloy, rigid PVC and polypropylene. These are typical of the specifications MPB can provide.

CP100 Calibration Cylinders conform to the 2014/68/EU Pressure Equipment Directive. The category of SEP applies, this is based on the process fluid being a Group 1 liquid with a vapour pressure of less than 0.5 bar and a cylinder volume of less than 200 bar litre.

### MPB SERIES CP100 FEATURES

- EASY TO READ
- CALIBRATED SCALES WITH TRACEABLE CERTIFICATES
- THREADED, OR FLANGED CONNECTIONS
- PRECISION BORE BOROSILICATE GLASS CYLINDERS
- PROTECTION COVERS AVAILABLE IF REQUIRED
- PERMANENTLY FIRED SCALES WITH WHITE BACKING TO GIVE EXCELLENT CLARITY
- PUMP SETTING GAUGE
- PUMP RATE CHECKING



## MPB SERIES CP100 CALIBRATION CYLINDER

<p><b>End Connections:</b> 316 Stainless steel, Super Duplex Stainless steel, Titanium, Hastelloy, Rigid PVC and Polypropylene, Threaded, or flanged to customer requirements. Fully certified where requested.</p> <p><b>Seals:</b> Nitrile, Viton, EPDM, etc</p> <p><b>Cylinder:</b> Precision bore borosilicate glass</p>	<p><b>Scale:</b> Permanently fired black ceramic</p> <p><b>Maximum Working Temperature:</b> 60°C RPVC 100°C Stainless steel</p> <p><b>Accuracy:</b> ± 0.5% of actual reading</p> <p><b>Options:</b> 316 Stainless Steel Safety Cover Mounting Brackets</p>
--	--

CAPACITY	CONNECTION	DRAWING NUMBER	MAXIMUM WORKING PRESSURE
50ml	½" NPT	MPVA 484S	14.4 bar g
100ml	½" NPT	MPVA 484E	11.8 bar g
150ml	½" NPT	MPVA 484T	11.5 bar g
200ml	½" NPT	MPVA 484U	10.0 bar g
250ml	½" NPT	MPVA 484F	10.0 bar g

For capacities up to 20ml - see MPBTB 087 (CP1200)

For capacities from 500ml to 10,000cc - see MPBTB 077 (CP110)

For alternative capacities and connections, please contact MPB Sales Office with precise requirements



Protective covers and mounting brackets are available for all capacities if required



*MPB Industries Ltd - Designers and Manufacturers of Scientific and Process Control Instrumentation*

Part of the Scientific Digital Imaging plc (SDI) group of companies  
Unit 1 Branbridges Ind Est, East Peckham, Kent TN12 5HF, UK, Tel: +44 (0)1622 872401  
mail@mpbflowmeters.com, www.mpbflowmeters.com



Due to the constant development and improvement of products, information may be altered or withdrawn without notice.