

Product Data Sheet



MPB SERIES 7200 VARIABLE AREA FLOWMETER

GENERAL INFORMATION

The MPB Series 7200 Variable Area Flowmeter has been designed to offer an economical solution for liquid flow measurements up to -1M³/min (1000 L/min, 60M³/hr)

The 7200 Variable Area Flowmeter can be supplied with either BSPPF, or metric solvent socket weld connections.

SERIES 7200 FEATURES

- EXCELLENT VALUE, SUPPLIED IN 5 LENGTHS
- HIGH FLOW RATES UP TO 1000 L/MIN H₂O (60M³/hr)
- DIRECT READING OF INSTANTANEOUS FLOW RATES
- EASY TO READ SCALE
- ABS THREADED, OR SOCKET WELD CONNECTIONS
- THE FLOW TUBE ASSEMBLY CAN EASILY BE REMOVED FROM THE FLOWMETER FOR CLEANING
- EASY INSTALLATION AND REMOVAL FROM
 PROCESS LINE
- GUIDED FLOATS TO GIVE VERY STABLE READINGS
- MATERIALS OF CONSTRUCTION OFFER WIDE COMPATIBILITY WITH A RANGE OF PROCESS MEDIUMS
- GOOD STANDARD WORKING
 PRESSURE RATINGS (UP TO 20 bar g)



- SCALES SUITABLE FOR 7 YEAR EXPOSURE TO DIRECT SUNLIGHT
- 10:1 TURN DOWN
- GOOD STANDARD CORROSION RESISTANCE

MPB SERIES 7200 VARIABLE AREA FLOWMETER

End Connectior		: Grev ABS	Weight:	20mm∅ - 120g
		Grey PVC Socket Weld		32mm∅ - 1.0kg
	Seals:	Viton		40mmØ - 2.0kg
	Metering Tube:	Clear SAN		63mmØ - 3.0kg
	Float:	316 Stainless steel		75mmØ - 4.0kg
	Guide Rod:	316 Stainless steel		Working Temperature: 60°C Working Pressure: up to 20 bar g
	Scale:	Permanently fired ceramic black	Accuracy:	± 5% FSD predicted
	Float: Guide Rod:	316 Stainless steel 316 Stainless steel	Maximum	75mm∅ - 4.0kg Working Temperature: 60°C Working Pressure: up to 20 bar g

STANDARD STOCK RANGES

RANGE (Water @ 20°C)			SIZE (mm)	CONNECTIONS		
L/hr	L/min	USGPM	Overall Length	Thread BSPP ABS	Socket Dia (mm) ABS	Grey PVC Socket Weld
40-400	0.7-7	-	200	G1⁄2"	20	½" nb
50-500	1-10	-	200	G1⁄2	20	½" nb
100-1000	2-20	0.4-4	230	G¾"	32	³⁄₄" nb
150-1500	2.5-25	0.7-7	230	G¾"	32	¾" nb
250-2500	5-50	1.0-10	230	G¾"	32	³⁄₄" nb
400-4000	6-60	1.6-16	290	G1"	40	1" nb
600-6000	10-100	2.5-25	290	G1"	40	1" nb
1-10 M3/H	16-160	4-40	350	G1½"	63	1½" nb
1.6-16 M3/H	25-250	7-70	350	G1½"	63	1½" nb
5-25 M3/H	40-400	10-100	430	G2"	75	2" nb
8-40 M3/H	130-650	30-170	430	G2"	75	2" nb
12-60 M3/H	200-1000	50-260	430	G2"	75	2" nb

MPB Industries Ltd - Designers and Manufacturers of Scientific and Process Control Instrumentation Part of SDI Group PLC Unit 1 Branbridges Ind Est, East Peckham, Kent TN12 5HF, UK, Tel: +44 (0)1622 872401 mail@mpbflowmeters.com, www.mpbflowmeters.com

Due to the constant development and improvement of products, information may be altered or withdrawn without notice.

MPBTB 073 lss 7